

Glass Cloth Masking Tape

GCTP Series

RoHS & REACH Compliant

Glass Cloth Tapes are made of 5 mil thick glass cloth film with 2 mil thick high temperature thermo-setting silicone adhesive. They are used in powder coating and the blasting industry to mask areas that do not require coating or blasting. They can be removed cleanly without leaving any residue. These masking tapes are packaged on a 3" core and are 36 yards long.


Applications

- Powder Coating and Thermal Spray
- Sandblasting
- Sealing of High Temperature Ducts and Chambers

Product Specifications ⁽¹⁾

Color	White	
Adhesion Type	Silicone	
Film Thickness	5 Mil	ASTM D-3652
Adhesive Thickness	2 Mil	
Total Thickness	7 Mil	ASTM D-3652
Tensile Strength	180 lbs./in	ASTM D-3759
Elongation	5 %	ASTM D-3759
Dielectric Strength	3,000 volts	ASTM D-149
Operating Temperature	-73°C (-100°F) to 260°C (500°F)	
Length	36 Yards	
Adhesion to Steel	40 Oz./in	ASTM D-3330
Core	3 in. Plastic Core	

⁽¹⁾ Specifications are subject to change at any time. If you have any questions, please contact us for the latest update.



Bertech® makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its this product for any particular purpose, nor does Bertech® assume any liability whatsoever arising out of the application or use of this product. It is ultimately the responsibility of the customer to determine a product's suitability for a particular application.



MaskingProducts

640 Maple Ave

Torrance, CA 90503

Phone: (310) 787-0337

Email: sales@maskingproducts.net

www.maskingproducts.net

PRODUCT DATA SHEET